HD-Series



STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

STAINLESS STEEL CARRY HANDLE
portable and space-saving compact design

ELECTRIC MOTOR - 1400 RPM, 4-POLE
slower motor RPMs last longer, run quieter and allow for better in-let suction capabilities

TOTAL-STOP SYSTEM
automatic standby of the motor reduces noise and power consumption when not in use

DETERGENT SUCTION INTAKE
direct dispensing of cleaning agent - without additional accessories

600180 HD 12/130 TS

► **ACCESSORIES** | starting on page 22

EQUIPMENT

- Quick release plug-in system D12
- Total-Stop system
- Pressure regulation
- Cleaning Agent Intake
- Direct suction: Suction height HD 9/80 TS: 1.5 m | HD 12/130 TS: 2.5 m
- High-pressure hose with Twist-Stop screw connection



MODEL		HD 9/80 TS	HD 12/130 TS
Ord.no.		**600130**	**600180**
TECHNICAL SPECIFICATIONS			
Operating pressure	bar | MPa	30-80 | 3-8	30-130 | 3-13
Water output	l/min | l/h	9 | 540	11 | 660
Admissible overpressure	bar | MPa	90 | 9	145 | 14.5
Motor speed	Rpm	1400	1400
Connection	V | ~ | Hz | A	230 | 1 | 50 | 7.5	230 | 1 | 50 | 13.5
Power intake | Power output	kW	1.6 | 1.0	2.9 | 2.2
Power supply cable	m	5	5
Dimensions L x W x H	mm	470 | 230 | 320	500 | 240 | 320
Weight	kg	24	31
EQUIPMENT			
High-pressure hose	m | Ord.no.	10 (DN6) | 43416	10 (DN6) | 43416
Trigger gun with safety catch	Model | Ord.no.	M2000 | 12481	M2000 | 12481
Lance with regulating nozzle	Nozzle | Ord.no.	● 042 | 12436-M20042	● 042 | 12436-M20042
Lance with Dirtkiller	Nozzle | Ord.no.	● 042 | 12438-042	● 042 | 12438-042



