



Air Conditioner Compressors

GMCC

ROTARY COMPRESSORS





Air Conditioner Compressors

GMCC

Series	Typical Model	Displ (cm³/rev)	Cooling Capacity (W)	Cooling Capacity (Btu/h)	Power (W)	COP (W/W)	Compressor Height (mm)	Discharge Pipe ID (mm)	Suction Pipe ID (mm)	Remark		
										Test Condition	Refrigeration	
SN	ASN98D22UFZ	9.8	2900	9895	736	3.94	251	8.1	12.9	SEER60	R410A	DC INVERTER SINGLE CYLINDER
	ASN98D32UFZ	9.8	2900	9895	729	3.98	251	8.1	12.9			
	ASN108D22UFZ	10.8	3250	11089	825	3.94	251	8.1	12.9			
	ASN108D32UFZ	10.8	3250	11089	817	3.98	251	8.1	12.9			
SM	ASM89D12UFZ	8.9	2650	9042	694	3.82	259	8.1	12.9			
	ASM89D1UFZ	8.9	2650	9042	663	4.00	259	8.1	12.9			
	ASM98D17UFZA	9.8	2900	9895	747	3.88	283	8.1	12.9			
	ASM98D1UFZA	9.8	2900	9895	721	4.02	283	8.1	12.9			
	ASM108D13UFZ	10.8	3205	10935	846	3.79	283	8.1	12.9			
M1	ASM108D1UFZA	10.8	3205	10935	797	4.02	283	8.1	12.9			
	DA89M1C-30FZ	8.9	2645	9025	665	3.98	240	8.1	12.9			DC INVERTER TWIN CYLINDER
	DA98M1C-30FZ	9.8	2900	9918	735	3.95	278	8.1	12.9			
	DA130M1C-31FZ	13.0	3905	13355	995	3.90	278	8.1	12.9			
S1	DA130M1C-28FZ	13.0	3930	13409	990	3.95	278	8.1	12.9			
	DA115S1B-27FZ	11.5	3380	11533	840	4.02	279	8.1	12.9			
	DA131S1B-31FZ	13.1	3930	13410	1005	3.90	279	8.1	12.9			
	DA131S1B-28FZ	13.1	3934	13423	993	3.96	279	8.1	12.9			
	DA150S1C-20FZ	15.0	4490	15320	1145	3.90	279	8.1	12.9			
	DA150S1C-28FZ	15.0	4515	15405	1135	3.98	279	8.1	12.9			
S2	DA200S2C-10MT	20.2	6115	20864	1745	3.50	322	9.8	16.2			
	DA200S2C-30MT	20.2	6110	20847	1720	3.55	322	9.8	16.2			
	DA230S2C-31MT	23.0	7000	23884	1930	3.63	322	9.8	16.2			
	DA250S2C-30MT	25.1	7700	26272	2110	3.65	322	9.8	16.2			

Series	Typical Model	Displ (cm³/rev)	Cooling Capacity (W)	Cooling Capacity (Btu/h)	Power(W)	COP(W/W)	Capacitor (µF/V)	Compressor Height (mm)	Discharge Pipe ID (mm)	Suction Pipe ID (mm)	Remark		
											test condition	refrigeration	
SM	HSM135V1UFZ	13.3	2330	7950	700	3.33	25/370	292	8.1	12.9	ASH	R22	1φ-50Hz-220/240V
	HSM140V1UFZ	13.9	2435	8308	735	3.32	25/370	292	8.1	12.9			
	HSM145V1UFZ	14.6	2570	8769	775	3.32	25/370	292	8.1	12.9			
	HSM150V5UFZ	15.1	2640	9008	800	3.30	25/370	292	8.1	12.9			
	HSM155V1UFZ	15.3	2665	9093	815	3.27	25/370	292	8.1	12.9			
	HSM160V5UFZ	15.8	2755	9400	840	3.28	25/370	292	8.1	12.9			
	HSM165V1UFZ	16.4	2845	9707	870	3.27	30/370	292	8.1	12.9			
	HSM185V1UFZ	18.7	3245	11072	980	3.30	35/370	301	8.2	12.9			
	HSM190V1UFZ	19.2	3345	11413	1040	3.22	35/370	301	8.2	12.9			
	HSM195V1UFZ	19.7	3460	11806	1040	3.22	35/370	301	8.2	12.9			
	HSM200V1UFZ	20.1	3480	11874	1070	3.25	35/370	301	8.2	12.9			
	HSM210V4UFZ	20.9	3605	12300	1120	3.22	40/370	301	8.2	12.9			
M2	HSM215V4UFZA	21.4	3720	12693	1155	3.22	40/370	301	8.2	12.9	GX	R22	1φ-50Hz-220/240V
	PH190M2A-4FTL1	19.1	3764	12842	840	4.48	35/370	293	8.2	12.9			
	PH195M2A-4FTL1	19.5	3863	13180	862	4.48	35/370	293	8.2	12.9			
	PH200M2A-4FTL1	20.0	3962	13518	884	4.48	35/370	293	8.2	12.9			
	PH210M2A-4FTL1	20.9	4160	14194	930	4.48	35/370	293	8.2	12.9			
	PH290G2C-4KUL1	28.7	5760	19653	1280	4.50	55/400	310	9.8	12.9			
G2	PH300G2C-4KUL1	29.7	5970	20370	1320	4.52	55/400	310	9.8	12.9			
	PH310G2C-4KUL	30.8	6135	20933	1370	4.48	55/400	310	9.8	12.9			
	PH300G2CS-4MUL	39.8	8095	27620	1800	4.50	55/400	354	9.8	12.9			
M3	PH410M3CS-4MUL	41.0	8270	28217	1880	4.40	60/400	381	9.8	16.2			
	PH420M3CS-4MUL	42.0	8500	29002	1930	4.40	60/400	381	9.8	16.2			
	PH430M3CS-4MUL1	42.6	8675	29599	1970	4.40	60/400	381	9.8	16.2			
	PH440M3CS-4MUL1	43.6	8815	30077	2015	4.37	60/400	381	9.8	16.2			

Series	Typical Model	Displ (cm³/rev)									Suction Pipe ID (mm)	Remark		
			Cooling Capacity (W)	Cooling Capacity (Btu/h)	Power(W)	COP(W/W)	Capacitor (µF/V)	Compressor Height (mm)	Discharge Pipe ID (mm)					
										test condition		refrigeration		
SM	DSM180V1UDZ	18.1	2990	10200	690	4.30	30/370	285	8.2	9.8	GX	R290	1φ-50Hz-220/240V	
SF	DSF240V1UFT	23.9	3980	13580	895	4.45	35/370	292	8.2	12.9				
	DSF340V1UFT	34.0	5720	19445	1315	4.35	35/370	325	9.8	12.9				
SG	KSG270V1UMU2	27.0	8350	28485	1950	4.28	50/400	344	9.8	16.2	SEER60	R32	DC Inverter	
SM	DSM160D19UDZ	15.8	2750	9381	670	4.10		270	8.1	9.8				
	DSM180D19UDZ	17.9	3100	10575	760	4.10		270	8.1	9.8				
SM	KSM89D16UEZ2	8.9	2780	9484	730	3.77		254	8.1	9.8				
	KSM108D10UEZ2	10.8	3385	11548	885	3.82		278	8.1	9.8				
	KSM130D12UFZ2	13.0	4065	13867	1090	3.75		278	8.1	12.9				
TF	KTF250D1UMT2	25.0	7965	27172	2210	3.60		322	9.8	16.2		R32	DC INVERTER TWIN CYLINDER	

Copper Tubes & Fittings

AC/R Spare Parts & Accessories

Compressors

Refrigerant & Chemicals

AC Installation

AC/R Service Tools & Equipment

Motors & Fans

AC Units

Auto AC Parts



Air Conditioner Compressors

Series	Typical Model	Displ (cm³/rev)	Cooling Capacity (W)	Cooling Capacity (Btu/h)	Power(W)					Suction Pipe ID (mm)	Remark		
						COP(W/W)	Capacitor (µF/V)	Compressor Height (mm)	Discharge Pipe ID (mm)				
											test condition	refrigeration	
GO	PH60G0C-4BZDE	6.0	985	3361	345	2.86	20/370	241	6.5	9.8	ASH	R22	1φ-50Hz-220/240V
	PH104G0C-4BZDE	10.4	1745	5954	580	3.01	25/370	259	6.5	9.8			
	PH108G0C-4BZDE	10.8	1830	6244	590	3.10	25/370	259	6.5	9.8			
SN	HSN82V1UBZ	8.2	1455	4964	485	3.00	25/370	251	6.5	9.8			
M1	PH130M1C-4DZDE2	13.1	2225	7592	725	3.07	25/370	270	9.8	6.5			
G1	PH135G1C-4DZDE1	13.3	2270	7745	725	3.13	30/370	285	9.8	8.2			
SM	HSM150V4UDZ	15.1	2680	9144	885	3.03	30/370	292	8.1	12.9			
	HSM165V4UDZ	16.4	2865	9775	910	3.15	30/370	292	8.1	9.8			
	HSM200V4UDZ	20.1	3525	12027	1175	3.00	35/370	301	9.8	12.9			
	HSM215V4UDZ	21.4	3700	12624	1175	3.15	35/370	301	9.8	12.9			
	HSM215V4UDZ	21.4	3700	12624	1175	3.15	35/370	301	9.8	12.9			
	HSM215V4UDZ	21.4	3700	12624	1215	3.05	35/370	301	8.2	12.9			
	HSM215V4UDZ	21.4	3700	12624	1215	3.05	35/370	301	8.2	12.9			
M2	PH225M2A-4FT	22.4	3915	13357	1265	3.10	35/370	293	8.2	12.9			
	PH240M2A-4FT1	24.0	4195	14346	1353	3.10	35/370	293	8.2	12.9			
	PH290M2A-4FT1	28.8	5090	17367	1650	3.08	35/370	348	9.8	12.9			
	PH295M2AS-4KU1H	29.7	5350	18253	1715	3.12	45/370	348	9.8	12.9			
G2	PH310M2AS-4KTH	31.0	5565	18988	1750	3.18	44/370	348	9.8	12.9			
	PH300G2C-4KU1	29.8	5340	18220	1645	3.25	55/400	297	9.8	12.9			
	PH310G2C-4KU1	30.8	5515	18817	1695	3.25	55/400	310	9.8	12.9			
	PH340G2C-4KU1	33.7	6030	20574	1865	3.23	60/400	310	9.8	12.9			
	PH340G2C-4KU	33.7	6050	20643	1805	3.35	60/400	310	9.8	12.9			
	PH360G2C-4MU1	36.0	6475	22093	2005	3.23	50/400	324	9.8	16.2			
	PH370G2CS-4MU1	37.0	6650	22690	2065	3.22	50/400	324	9.8	16.2			
	PH370G2C-4MU	37.0	6660	22724	2020	3.30	50/400	324	9.8	16.2			
	PH400G2CS-4MU1	39.8	7100	24225	2225	3.15	50/400	354	9.8	16.2			
	PH400G2CS-4MU	39.8	7095	24208	2215	3.20	50/400	354	9.8	16.2			
	PH420G2CS-4KU1	42.0	7420	25317	2390	3.10	50/400	354	9.8	16.2			
	PH420G2CS-4MU	42.0	7555	25778	2365	3.20	50/400	354	9.8	16.2			
X3	PH440G2CS-4MU	43.6	7810	26648	2390	3.27	50/400	354	9.8	16.2			
	PH460X3CS-4MU1	45.9	45.9	45.9	45.9	45.90	45.9	45.9	45.9	45.9			
SN	PH480X3CS-4MU1	47.9	47.9	47.9	47.9	47.90	47.9	47.9	47.9	47.9			
	HSN98N1UBR	9.8	2075	7080	645	3.22	15/370	251	8.1	9.8			
GO	HSN10N1VBZ	10.2	2100	7065	665	3.16	15/370	251	8.1	9.8			
	PH108G0C-3BZDU	10.8	2200	7506	710	3.10	25/370	259	6.5	9.8			
M1	PH120M1C-3DZDU1	12.2	2490	8496	790	3.15	30/370	266	8.2	9.8			
	PH130M1C-3DZDU1	13.1	2660	9076	850	3.13	30/370	270	6.5	9.8			
G1	PH140G1C-3DZDU1	13.9	2890	9861	895	3.23	35/370	285	8.2	9.8			
	PH150G1C-3DZDU2	15.1	3135	10697	990	3.17	35/370	285	8.2	9.8			
	PH160G1C-3DZDU1	16.0	3280	11191	1015	3.23	35/370	285	8.2	9.8			
	PH165G1C-3FZDU1	16.5	3475	11857	1060	3.28	40/370	285	8.2	9.8			
SM	HSM170N2UDZ	17.0	3495	11925	1075	3.25	40/370	292	8.1	9.8			
G1	PH175G1C-3FTU	17.6	3710	12659	1140	3.25	35/370	294	8.2	12.9			
	PH180G1C-3FTU1	18.1	3800	12966	1195	3.18	40/370	292	8.2	12.9			
	PH195G1C-3FTU1	19.6	4155	14090	1310	3.17	35/370	292	8.2	12.9			
M2	PH225M2C-3FTU1	22.4	4770	16275	1505	3.17	40/370	292	8.2	12.9			
	PH240M2A-3FTU1	23.9	5140	17538	1580	3.25	40/370	292	8.2	12.9			
	PH250M2A-3FTU2	25.0	5400	18425	1685	3.20	40/370	333	9.8	12.9			
	PH260M2AS-3KU1	26.1	5625	19193	1815	3.10	40/400	333	9.8	12.9			
X2	PH290X2C-3FTU1	29.0	6130	20916	1990	3.80	50/370	311	9.8	12.9			
G2	PH310G2C-3KU1	31.0	6700	22860	2000	3.35	55/400	310	9.8	12.9			
	PH330G2C-3MUU	32.8	7150	24396	2135	3.35	55/400	297	9.8	16.2			
	PH330G2C-3MUU1	32.8	7040	24020	2215	3.18	55/400	297	9.8	16.2			
	PH340G2C-3MUU	33.7	7340	25044	2190	3.35	55/400	297	9.8	16.2			
	PH340G2C-3MUU1	33.7	7280	24839	2275	3.20	55/400	310	9.8	16.2			
	PH360G2C-3KU1	36.0	7685	26221	2405	3.20	55/400	310	9.8	12.9			
X3	PH370G2C-3MUU1	37.0	8020	27364	2505	3.20	55/400	372	9.8	16.2			
	PH401X3CS-3MUU	40.2	8745	29840	2690	3.25	60/400	372	9.8	16.2			
	PH441X3CS-3MUU	43.5	9470	32312	2915	3.25	60/400	292	9.8	16.2			
M1	EH130M1C-1DZDU1	13.1	2700	9212	850	3.17	45/250	266	8.2	9.8			
	EH170M1B-1DZ1	16.8	3500	11942	1120	3.13	55/250	285	8.2	9.8			
											1φ-60Hz-115V		



Air Conditioner Compressors

Series	Typical Model	Displ (cm³/rev)	Cooling Capacity (W)	Cooling Capacity (Btu/h)	Power(W)	COP(W/W)	Capacitor (µF/V)	Compressor Height (mm)	Discharge Pipe ID (mm)	Suction Pipe ID (mm)	Remark		
											test condition	refrigeration	
SN	ASN82V1UDZ	8.2	2045	6977	675	3.03	25/370	251	8.1	9.8	ASH	R410A	1φ-50Hz-220/240V
	ASN86V1UDZ	8.6	2160	7370	725	2.98	25/370	251	8.1	9.8			
	ASN89V1UDZ	8.9	2260	7711	765	2.95	25/370	251	8.1	9.8			
M1	PA98M1C-4DZDE1	9.8	2340	7984	780	3.00	25/370	279	8.1	9.8			
	PA103M1C-4DZDE	10.3	2470	8428	820	3.01	25/370	279	8.1	9.8			
	PA108M1C-4DZDE2	10.8	2570	8769	860	2.98	25/370	279	8.1	9.8			
G1	PA118M1C-4FZ2	11.8	2780	9485	955	2.91	25/370	279	8.1	9.8			
	PA130G1C-4FT1	13.0	3155	10765	1070	2.95	35/370	298	8.1	9.8			
	PA140G1C-4FT1	13.9	3400	11601	1155	2.95	35/370	298	8.2	12.9			
X2	PA145G1C-4FT1	14.7	3585	12232	1240	2.89	35/370	298	8.1	12.9			
	PA150G1C-4FT	15.1	3700	12625	1275	2.90	35/370	298	8.1	12.9			
	PA150X2C-4FT	15.1	3660	12514	1260	2.90	35/370	299	8.1	12.9			
M2	PA160X2C-4FT	16.0	3910	13341	1350	2.90	35/400	299	8.1	12.9			
	PA170M2C-4ET2	17.1	4190	14295	1375	3.05	35/400	299	8.1	12.9			
	PA185M2C-4FT2	18.5	4495	15335	1500	3.00	35/400	299	8.1	12.9			
G2	PA200M2AS-4KU2	19.9	4975	16975	1670	2.98	45/400	340	8.1	12.9			
	PA215M2CS-4KT2	21.4	5285	18030	1760	3.00	50/370	340	8.1	12.9			
	PA225M2CS-4KU2	22.4	5500	18755	1835	3.00	50/370	340	8.1	12.9			
X3	PA240M2CS-4KU1	23.9	5840	19926	1980	2.95	50/370	340	8.1	12.9			
	PA250G2C-4FU1	25.1	6245	21352	2095	2.98	60/400	310	9.8	12.9			
	PA270G2C-4FT1	27.0	6665	22741	2220	3.00	60/400	310	9.8	12.9			
SM	PA290G2CS-4MU1	28.7	7270	24805	2420	3.00	50/400	344	9.8	16.2			
	PA331X3CS-4MU1	32.6	8190	27944	2715	3.02	55/400	382	9.8	16.2			
G1	ASM106V1VDZ	9.8	3080	10509	725	4.25	25/370	292	8.1	12.9	GX	R410A	1φ-50Hz-220/240V
	ASM135V1VFT	13.3	3775	12880	910	4.27	35/370	292	8.1	12.9			
	PA145G1C-4FTL	14.7	4140	14125	1010	4.10	35/370	298	8.1	12.9			
M2	PA150M2A-4FTL	15.0	4300	14672	1025	4.20	35/370	299	8.1	12.9			
	PA165M2AS-4KUL	16.5	4750	16245	1110	4.28	35/370	340	8.1	12.9			
	PA190M2AS-4KTL1	19.1	5460	18630	1270	4.30	40/370	340	8.1	12.9			
SG	PA240M2CS-4KUL	23.9	6890	23509	1660	4.15	50/370	340	8.1	12.9			
	ASG240V1VMU	23.9	6950	23713	1605	4.33	50/400	310	9.8	16			
	PA250G2CS-4MUL	25.1	7315	24959	1690	4.32	50/400	344	9.8	16.2			
G2	PA270G2CS-4MUL	27.0	7865	26835	1815	4.33	60/400	344	9.8	16.2			
	PA280G2CS-4MUL	27.9	8135	27757	1880	4.33	60/400	344	9.8	16.2			
	PA290G2CS-4MUL	28.7	8485	28951	1965	4.32	60/400	344	9.8	16.2			
X3	PA311X3CS-4MUL	30.5	8880	30299	2090	4.25	55/400	382	9.8	16.2			
	PA331X3CS-4MUL	32.6	9510	32448	2225	4.27	55/400	382	9.8	16.2			

Series	Typical Model	Displ (cm³/rev)	Cooling Capacity (W)	Cooling Capacity (Btu/h)	Power(W)	COP(W/W)	Capacitor (µF/V)	Compressor Height (mm)	Discharge Pipe ID (mm)	Suction Pipe ID (mm)	Remark		
											test condition	refrigeration	
SN	ASN68N1UDZ	6.8	2050	6995	665	3.08	20/370	251	8.1	8.1	ASH	R410A	1φ-60Hz-208/230V
	ASN82N1UDZ	8.2	2475	8445	825	3.00	25/370	251	8.1	8.1			
	ASN89N1UDZ	8.9	2725	9298	867	3.14	25/370	251	8.1	8.1			
M1	PA98M1C-3FZD	9.8	2900	9895	930	3.12	35/370	278	8.1	8.1			
SM	ASM106N1VDZ	10.6	3640	12420	850	4.28	40/370	292	8.1	8.1			
M1	PA118M1C-3FZU	11.8	3390	11567	1125	3.01	35/370	278	8.1	8.1			
G1	PA150G1C-3FTU1	15.1	4445	15166	1505	2.95	40/370	297	8.1	8.1			
	PA150M2AS-3KU	15.0	4405	15030	1445	3.05	45/370	325	9.8	9.8			
	PA155M2A-3ETL	15.5	4650	15866	1485	3.13	50/370	303	9.8	9.8			
M2	PA160M2A-3ET	16.0	4795	16361	1545	3.10	45/370	303	9.8	9.8			
	PA165M2C-3ETU	16.5	4820	16446	1625	2.97	40/370	303	9.8	9.8			
	PA170M2A-3FT1	17.1	5055	17248	1645	3.07	40/370	303	9.8	9.8			
G2	PA200M2CS-3MUU1	19.8	5800	19790	1940	2.99	50/370	344	9.8	9.8			
	PA210M2C-3ETU2	20.8	6160	21018	2035	3.03	50/370	322	9.8	9.8			
M2	PA226G2C-3MT	22.3	6740	22997	1285	3.08	60/400	310	9.8	9.8			
	PA241G2C-3MT	24.0	7200	24566	1225	3.10	60/400	310	9.8	9.8			
X3	PA250M2CS-3MUU1	25.0	7445	25402	2500	2.98	60/370	344	9.8	9.8			
	PA270X3CS-3MUU	26.9	8160	27842	2700	3.02	55/400	382	9.8	9.8			
	PA291X3CS-3MTU	28.8	8650	29514	2805	3.08	55/400	382	9.8	9.8			
SK	ASK49E1UZR	4.9	1450	4947	490	2.96	35/250	237	8.1	9.8			
	ASK50E1UZZ	5.0	1505	5100	510	2.95	35/250	237	8.1	9.8			
	ASK50E1UZZA	5.0	1505	5100	510	2.95	35/250	231	8.1	9.8			
SN	ASN68E1UZZ	6.8	2080	7097	686	3.03	45/250	229	8.1	9.8			
SM	ASM113E1UDZ	11.3	3340	11396	1085	3.08	60/250	292	8.1	9.8			
SK	ASK46E1VZR	4.6	1560	5320	397	3.93	35/250	237	8.1	9.8	GX	R410A	1φ-60Hz-115V
SN	ASN46E1VZJ	4.6	1550	5320	385	4.03	35/250	238	8.1	9.8			
	ASN54E1VZJ	5.4	1865	5100	455	4.10	35/250	238	8.1	9.8			
	ASN58E1VZJ	5.8	2005	6860	497	4.03	40/250	238	8.1	9.8			
SM	ASN71E1VBZ	7.1	2455	8376	595	4.13	45/250	247	8.1	9.8			
	ASN84E1VBZ	8.4	2910	9929	705	4.13	50/250	247	8.1	9.8			
	ASN86E1VBZ	8.6	2995	10219	725	4.13	50/250	247	8.1	9.8			
SM	ASN89E1VBZ	8.9	3100	10577	775	4.00	50/250	247	8.1	9.8			
	ASM106E2VEZ	10.6	3700	12624	860	4.30	70/250	292	8.1	12.9			
	ASM130E1VDT	13.0	4490	15320	1070	4.20	70/250	292	8.1	9.8			

Copper Tubes & Fittings

AC/R Spare Parts & Accessories

Compressors

Refrigerant & Chemicals

AC Installation

AC/R Service Tools & Equipment

Motors & Fans

AC Units

Auto AC Parts



COMPRESSOR STANDANRD PACKAGE

We have export and domestic package types, see the right pictures

20-foot container=20Boxes



Export Packing

Package Dimensions		1	2	3	4	5	6	7	8	9	10	11	12
Export	L(m)	1.144	1.144	1.144	1.144	1.144	1.144	1.144	1.144	1.144	1.144	1.144	1.144
	W(m)	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108	1.108
	H(m)	0.99	0.99~1.05	0.78~0.86	0.78~0.86	0.96~1.01	0.83~0.86	0.75~0.84	0.8~1.0	0.80	0.76~0.97	0.87~1.03	0.83~0.93
Q'ty/Gr. Wt./Box	48-108 SK	120/1020~1140											
	48-108 SN		120/1140~1260										
	125-215 SM(φ 150)			80/690~1020									
	125-215 SM(φ 176)				60/780~1155								
	48-108G0C					120/995~1145							
	125-215 G1(φ 150)						80/840~1085						
	125-215 G1(φ 176)						60/730~830						
	79-180 X1(φ 150)							80/795~1055					
	108-180 X1(φ 176)							60/680~805					
	79-130 M1 (φ 150)								80/690~1020				
	108 M1C (φ 176)									60/740			
	130-210 S1 (φ 150)												
	130-340 X2/M2										60/780~1155		
	251-480 X3											48/950~1270	
	270-440 G2												48/850~1045

Note: Gr. Wt.---- The range of Gross Weight is the weight when packing models, the above data could only be used as a reference; Unit:kg.

Data can be subject to change without notice.

Package Dimensions		1	2	4	5	Package Dimensions		1	2	4	5
Export	L(m)	1.144	1.144	1.144	1.144	Q'ty/Gr. Wt./Box	48-108SK	120/1020~1140			
	W(m)	1.108	1.108	1.108	1.108		48-108SN		120/1140~1260		
	H(m)	0.99	0.99~1.05	0.78~0.86	0.78~0.86		125-215 SM(φ 150)			80/690~1020	
							125-215 SM(φ 176)				60/780~1155



COMPRESSOR ACCESSORIES

Accessories		Internal OLP Fixed-frequency Model	External OLP Fixed-frequency Model	AC /DC Inverter Model	
				Needing Thermal Sensor	No Thermal Sensor
Terminal Cover					
					
					
Terminal Packing					
					
					
Terminal Nut					
Terminal Nut Washer					
External OLP					
Rubber Cushion (3 Purchase)					
					
					
					